

Dirt, oil, and debris that collect in parking lots and paved areas can be washed into the storm sewer system and eventually enter local waterbodies.

- Sweep up litter and debris from sidewalks, driveways and parking lots, especially around storm drains.
- Cover grease storage and dumpsters and keep them clean to avoid leaks.
- Report any chemical spill to the local hazardous waste cleanup team.
  They'll know the best way to keep spills from harming the environment.

Erosion controls that aren't maintained can cause excessive amounts of sediment and debris to be carried into the stormwater system. Construction vehicles can leak fuel, cil, and other hamful fluids that can be picked up by stormwater and deposited into local waterbodies.

- Divert stomwater away from disturbed or exposed areas of the construction site.
- Install silt fences, vehicle mud removal areas, vegetative cover, and other sediment and erosion controls and properly maintain them, especially after rainstorms.
- Prevent soil erosion by minimizing disturbed areas during construction projects, and seed and mulch bare areas as soon as possible.



Lack of vegetation on streambanks can lead to erosion. Overgrazed pastures can also contribute excessive amounts of sediment to local waterbodies. Excess fertilizers and pesticides can poison aquatic animals and lead to destructive algae blocms. Livestock in streams can contaminate waterways with bacteria, making them unsafe for human contact.

> Keep livestock away from streambanks and provide them a water source away from waterbodies.

 Store and apply manure away from waterbodies and in accordance with a nutrient management plan.

Vegetate riparian areas along waterways.

 Rotate animal grazing to prevent soil erosion in fields.
Apply fertilizers and pesticides according to label instructions to save money and minimize pollution.



Improperly managed logging operations can result in erosion and sedimentation.

 Conduct preharvest planning to prevent erosion and lower costs.
Use logging methods and equipment that minimize soil disturbance.
Plan and design skid trails, yard areas, and truck access roads to minimize stream crossings and avoid disturbing the forest floor.

minimize stream crossings and avoid disturbing the forest floor. Construct stream crossings so that they minimize erosion and physical

Expedite revegetation of cleared areas.

changes to streams.



Uncovered fueling stations allow spills to be washed into storm drains. Cars waiting to be repaired can leak fuel, oil, and other harmful fluids that can be picked up by stormwater.

- Clean up spills immediately and properly dispose of cleanup materials.
- Provide cover over fueling stations and design or retrofit facilities for spill containment.
- Properly maintain fleet vehicles to prevent oil, gas, and other discharges from being washed into local waterbodies.
  - Install and maintain oil/water separators.



A Tyco Infrastructure Services Company

## Town of Seabrook, New Hampshire



Stormwater Education Program



A Tyco Infrastructure Services Company Engineering and technology for the planet www.earthtech.com

## What is stormwater runoff?



Stormwater runoff occurs when precipitation from rain or snowmelt flows over the ground. Impervious surfaces like driveways, sidewalks, and streets prevent stormwater from naturally soaking into the ground.



# Why is stormwater runoff a problem?

Stormwater can pick up debris, chemicals, dirt, and other pollutants and flow into a storm sewer system or directly to a lake, stream, river, wetland, or coastal water. Anything that enters a storm sewer system is discharged untreated into the waterbodies we use for swimming, fishing, and providing drinking water.





## The effects of pollution

Polluted stormwater runoff can have many adverse effects on plants, fish, animals, and people.

- \* Sediment can cloud the water and make it difficult or impossible for aquatic plants to grow. Sediment also can destroy aquatic habitats.
- Excess nutrients can cause algae blooms. When algae die, they sink to the bottom and decompose in a process that removes oxygen from the water. Fish and other aquatic organisms can't exist in water with low dissolved oxygen levels.
- Bacteria and other pathogens can wash into swimming areas and create health hazards, often making beach closures necessary.
- Debris—plastic bags, six-pack rings, bottles, and cigarette butts-washed into waterbodies can choke, suffocate, or disable aquatic life like ducks, fish, turtles, and birds.
- Household hazardous wastes like insecticides, pesticides, paint, solvents, used motor oil, and other auto fluids can poison aquatic life. Land animals and people can become sick or die from eating diseased fish and shellfish or ingesting polluted water.

Polluted stormwater often

affects drinking water

sources. This, in turn, can

affect human health and

increase drinking water

H

treatment costs.



A Tyco Infrastructure Services Company

## Stormwater Pollution Solutions





your pet,

Pet waste can be a major source o bacteria and excess nutrients in local waters. When walking

remember to pick up the

waste is the best disposal method. Leaving pet waste

on the ground increases public health risks by

the storm drain and eventually into local

waterbodies

allowing harmful bacteria and nutrients to wash into

waste and dispose of it properly. Flushing pet

Recycle or properly dispose of household products that contain chamicali, such as insecticides, politicides, paint, idvanti, and used motor cel and other auto Raidi. Doe't pour them onto the ground or into storm deaini.



and pesticides applied to lawns and gardens wash off and pollute streams. In addition, yard dippings and leaves can wash into storm drains and contribute nutrients and organic matter to streams.

- Don't overwater your lawn. Consider using a soaker hose instead of a sprinkler.
- Use pesticides and fertilizers sparingly. When use is necessary, use these chemicals in the recommended amounts. Use organic mulch or safer pest control methods whenever possible.
- \* Compost or mulch yard waste. Don't leave it in the street or sweep it into storm drains or streams
- \* Cover piles of dirt or mulch being used in landscaping projects.


### Residential landscaping

Permeable Pavement-Traditional concrete and asphalt don't allow water to soak into the ground. Instead these surfaces rely on storm drains to divert unwanted water. Permeable pavement systems allow rain and snowmelt to soak through decreasing stormwater runoff.

Rain Barrels\_You can collect rainwater from rooftops in mosquitoproof containers. The water can be used later on lawn or garden areas

Rain Gardens and Grassy Swales-Specially designed areas planted





Vegetated Filter Strips-Filter strips are areas of native grass or plants created along roadways or streams. They trap the pollutants stormwater picks up as it flows across driveways and streets.

#### Auto care

Washing your car and degreasing auto parts at home can send detergents and other contaminants through the storm sewer system. Dumping automotive fluids into storm drains has the same result as dumping the materials directly into a waterbody.

\* Use a commercial car wash that treats or recycles its wastewater, or wash your car on your yard so the water infiltrates into the ground.

 Repair leaks and dispose of used auto fluids and batteries at designated drop-off or recycling locations.

Septic systems Leaking and poorly maintained

septic systems release nutrients and pathogens (bacteria and viruses) that can be picked up by stormwater and discharged into nearby waterbodies Pathogens can cause public health problems and environmental concerns.

- Inspect your system every 3 years and pump your tank as necessary (every 3 to 5 years).
- Don't dispose of household hazardous waste in sinks or toilets.

